



FACES Peeled Gurjan Veneer

Faces

**INNER LAYERS** 100% Premium Hardwood

**GLUE** Phenol Formaldehyde (PF)

## RECOMMENDED APPLICATIONS







Indoor Furniture







Suntree Solid BWR grade plywood is a preservative-treated, water resistant plywood, manufactured from select hardwood timber as per IS: 303 – 1989 specifications. It is made from selected hardwood veneers and is bonded with extended superior quality Phenol Formaldehyde (PF) Synthetic resin with the Pre-Press Technology. The superior bonding strength of the BWR-type Synthetic resin adds extra durability making it highly water resistant. The result is a high quality ply that can resist boiling water, cold water and climatic variations. It is also chemically impregnated for better resistance and to impart termite and borer resistant properties. These grades of plywood are widely used for Wall paneling, Furniture, Hoardings and Semi Exterior works. Suntree Solid BWR comes with 8 Years Warranty\*

| THICKNESS    | 6 MM  | 9 MM  | 12 MM | 16 MM  | 19 MM  | 25 MM  |
|--------------|-------|-------|-------|--------|--------|--------|
| NO. OF PLIES | 5 PLY | 7 PLY | 9 PLY | 11 PLY | 13 PLY | 17 PLY |



## **SUNTREE SOLID BWR (IS:303)**

TEST ANALYSIS REPORT (As Per IS:710-2010)

| TYPES OF TESTS  | REFERENCE VALUE            | OBSERVED VALUE             |  |
|---|----------------------------|----------------------------|--|
| Surface   | AA/AB/BB                   | AA                         |  |
| Resistance to water  3 cycle each cycle consisting of 3hrs at 60±2°C. in water and drying 8 hrs at 65±2°C | Pass Standard              | Confirmed                  |  |
| Modulus of Elasticity Parallel to Face Grain(Avg) Across the Face Grain (Avg)                             | 5000N/Sq.mm<br>2500N/Sq.mm | 6450N/Sq.mm<br>3800N/Sq.mm |  |
| Modulus of Rupture  Parallel to Face Grain  (Avg) Across the Face  Grain Avg)                             | 40 N/Sq.mm<br>20 N/Sq.mm   | 42 N/Sq.mm<br>47 N/Sq.mm   |  |

## SUNTREE SOLID BWR (IS:303)



| Mycological Test | Pass Standard                         | Confirmed |
|------------------|---------------------------------------|-----------|
| Moisture Content | Not less than 5%<br>Not more than 15% | 10%       |



## **2** Suntree Woods Pvt. Ltd.,

62/ 2592, 2nd Floor, Saj Mahal Building, Madakkappillil Lane, Chittoor Road, Near South Railway Station, Ernakulam Dist., Kerala- 682 016

**9 1800 1211 791** (Toll free), +91 9778 920 958

